

COLLABORATE® Live 200



COLLABORATE Live solutions are the most versatile video collaboration room systems of their kind in the market. COLLABORATE Live 200 is a video collaboration system that captures an ultra wide-angle view for huddle spaces and small meeting rooms. High-quality audio and video collaboration solution for a huddle space budget.

- > One CHAT 150 speakerphone provides crystal-clear audio.
- > One UNITE® 50 EPTZ camera with professional-quality 4K resolution; a 120-degree, ultrawide angle field of view; and digital zoom.
- > User interface as intuitive and simple as familiar mobile or tablet devices.
- > Monitor, control, and audit Versa Pro CT with CONVERGENCE™ unified AV network management software
- > COLLABORATE Space is a powerful collaboration application with a full suite of audio, video, and meeting tools in a persistent space.

Crystal-Clear Audio

The CHAT® 150 speakerphone provides crystal-clear audio.

APPLICATIONS

- Video conferencing
- Audio conferencing
- Cloud video collaboration
- Wireless presentation
- Whiteboard

WORKSPACES

- Huddle spaces
- Executive offices
- Small meeting rooms



Made for small workspaces

The UNITE® 50 4K EPTZ camera—1080p30, 3x digital zoom with a 120-degree ultra wide-angle field-of-view captures all participants in the room.

Great Ideas Need to Be Seen - and Heard!™

COLLABORATE® Live 200

COLLABORATE LIVE 200

- COLLABORATE Live 200 codec appliance
- UNITE 50 4K EPTZ camera
- CHAT 150 speakerphone
- Power supplies, cables and accessories
- COLLABORATE Space application (90 days)
- One-year support and maintenance with warranty

COLLABORATE LIVE 200 CODEC APPLIANCE

- Video input: 1x USB 3.0
- Video output: 1x HDMI, 1x Display port
- Audio input: USB (Digital audio)
- Audio output: USB, S/PDIF
- USB: 4x USB 3.0

UNITE 50 CAMERA

- 120° ultra wide-angle field of view with EPTZ support
- Full auto-focus, limited-distortion lens
- Low-light 2D and 3D algorithm
- Image SNR as high as 55dB

CHAT 150 SPEAKERPHONE

- ClearOne HDConference™ audio processing
- Three built-in microphone array with 360° pickup
- Large loudspeaker with Max Output Level: 85 dB SPL @ 1 meter
- Wideband audio frequency response (20Hz-20kHz)

VIDEO CHARACTERISTICS

- Resolution up to 1080p @ 30 fps (Rx)
- H.261, H.263, H.263+/++
- H.264/AVC High Profile – up to 6Mbps
- H.264/SVC (Skype for Business)

AUDIO STANDARDS

- 20KHz: AAC-LD
- 14KHz: G.722.1 Annex C
- 7KHz: G.722, G.722.1
- 3.4KHz: G.711, G.723.1, G.728, G.729, AMR (3G)

DATA CHARACTERISTICS

- H.239 support for data sharing
- Resolution up to 1080p
- Data inputs via wireless, datapoint (HDMI-to-USB adapter)

CONTROL

- Web-based management and control
- Telnet API for 3rd-party control
- AMX and Crestron modules

PART NUMBER

- 930-3001-200

SALES AND INQUIRIES

Headquarters

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

US & Canada

Tel: 801.975.7200
Fax: 801.303.5711

International

Tel: +1.801.975.7200
global@clearone.com

Sales

Tel: 801.975.7200
sales@clearone.com

Tech Support

Tel: 801.974.3760
tech.support@clearone.com